



Filter Backwash Hydraulic Valve

2x2 Metal Body

IR-2x2-350-R

The BERMAD Model IR-2x2-350-R is a compact 3-port valve in a T configuration. It is double chambered, hydraulically operated, and diaphragm actuated. Designed for automatic backwashing of filtration systems, the BERMAD Model IR-2x2-350-R is available in Angle flow (A) and Straight flow (S) configurations.



Angle Flow



Straight Flow

Features and Benefits

- Line Pressure Driven
- Double Chambered Design
 - Wide application range
 - Requires low actuation pressure
 - Protected diaphragm
- Dynamic Sealing
 - Seals at very low pressure
 - Prevents seal friction and erosion
- Brass Body
 - Rigid construction, high stress resistance
- Short Valve Travel
 - Smooth changes of flow direction
 - Eliminates mixing of supply and waste water
- User- Friendly
 - Can be installed in various orientations
 - Simple in-line inspection and service



Typical Applications

- Automatic Backwash of Filter Batteries
 - Gravel Filters
 - Sand Filters
 - Disk Filters
 - Screen Filters
- Single Filter Autonomic Backwash System
- Angled or Straight Installations

[1] BERMAD Model IR-2x2-350-A-R allows flow into the filter, and switches closed upon pressure rise command, thereby blocking inlet to filter and enabling backwash flow from the filter.

[2] BERMAD Backwash Flow Control Valve Model IR-470-beKU

[3] BERMAD Water Meter Model WPH

[4] BERMAD Air Valve Model ARA-A-P-P



Trädgårdsteknik AB
Helsingborgsvägen 578
262 96 ÄNGELHOLM
Telefon: 0431-222 90
Telefax: 0431-222 70
info@tradgardsteknik.se
www.tradgardsteknik.se
