

SPRINKLERS

POP-UP 805



FEATURES AND BENEFITS

- Reliable impact plastic head for underground installation
- Color-coded bayonet nozzles for easy service
- Full- or part-circle pattern adjustment
- Diffuser screw breaks water into smaller droplets for uniform watering.
- Extra high 7.60 cm pop-up clearance
- Rugged ribbing case for maximum strength and durability – also provides anti-vandalism anchorage
- Sandproof seals and removable filter screen for easy maintenance

TECHNICAL DATA

- Spacing between sprinklers: up to 12.0 m
- Min/Max operating pressure: 2.0 - 4.0 bar
- 1/2" female water inlet

Pop-up plastic impact sprinkler



POPUP 805 Performance Table

Nozzle color (mm)	P (bar)	Q (m ³ /h)	D (m)
2.8 Orange	2.0	0.450	21
	3.0	0.550	23
	4.0	0.630	23
3.0 Red	2.0	0.510	22
	3.0	0.630	24
	4.0	0.720	25
3.2 Green	2.0	0.570	23
	3.0	0.700	24
	4.0	0.810	25
3.5 Blue	2.0	0.660	23
	3.0	0.810	24
	4.0	0.930	26
4.0* Black	2.0	0.850	24
	3.0	1.030	25
	4.0	1.180	26

* Standard nozzle



Postadress:

TRÄDGÅRDSTEKNIK AB
Helsingborgsvägen 578, Varalöv
262 96 ÄNGELHOLM

Telefon : 0431-222 90
Bg.nr : 5743-7980
Org.nr : 556409-6120

URL:

www.tradgardsteknik.se
E-postadress:
info@tradgardsteknik.se