

SPRINKLERS PRO-S™ SPRAYS



Pop-up 1/2" sprays are distinguished by their robust construction, rugged body and cap, co-molded seal and heavy duty retraction spring. The co-molded wiper seal ensures proper operation time after time with minimal flow by. Compatible with all standard female threaded nozzles.



FEATURES AND BENEFITS

- Co-molded wiper seal ensures a leak-free, full pop-up operation even in low-pressure conditions.
- Cartridge design allows for easy removal and cleaning.
- Treated with UV inhibitors for long life. Seal is microbe-resistant to reduce degradation and stick-ups.
- Accepts female threaded nozzles
- Ratcheting riser permits quick, easy alignment of spray pattern.
- Heavy-duty retraction spring – strongest spring in the industry for positive retraction in all soil conditions.
- Side inlet – standard on 12" (30.5 cm) model
- 6" model available with or without side inlet
- Wide selection of sizes – available in 2", 3", 4", 6" and 12" (5, 7.5, 10, 15 and 30.5 cm) models
- Pre-installed flush cap
- Optional in-stem pressure regulator – available for 4", 6" and 12" (10, 15 and 30.5 cm) models, factory preset at 40 Psi (2.8 bar)
- Optional in-stem check valve is installed in the field and holds up to 10" (3 m) of head pressure.
- Optional pre-installed nozzle guard

TECHNICAL DATA

- Operating pressure: 1.4 – 4.8 bar
- Flow rate: 0.6 bar, 1.9 – 17.5 l/m
- Inlet: 1/2" (1.3 cm) female threaded NPT

Postadress:

TRÄDGÅRDSTEKNIK AB
Helsingborgsvägen 578, Varalöv
262 96 ÄNGELHOLM

Telefon : 0431-222 90
Bg.nr : 5743-7980
Org.nr : 556409-6120

URL:

www.tradgardsteknik.se
E-postadress:
info@tradgardsteknik.se