






# 60P

AGG. 09/20

3~ 50 Hz. 400V	
<b>PERKINS</b>	
EU STAGE 0	
69 dB(A) @ 7 mt	
100 lt	

PRIME POWER		STAND-BY POWER	
kVA	kW	kVA	kW
<b>60</b>	<b>48</b>	<b>66</b>	<b>52,8</b>

ENVIRONMENTAL CONDITIONS	
Temperature	<b>40° C</b>
Height	<b>1000 mslm</b>
Humidity	<b>60%</b>

**OPEN VERSION B50**
**SOUNDPROOF VERSION C50**


The image is only for demonstration purposes

WEIGHT	DIMENSIONS		
	L [mm]	W [mm]	H [mm]
<b>800</b>	<b>1650</b>	<b>850</b>	<b>1650</b>

WEIGHT	DIMENSIONS		
	L [mm]	W [mm]	H [mm]
<b>960</b>	<b>2000</b>	<b>850</b>	<b>1275</b>

## TECHNICAL DETAILS

ELECTRICAL DATA	Electrical system type	3F+N	~
	Power factor	0,8	φ
	Voltage	400	V
	Frequency	50	Hz
	PRP Ampere rating	86,6	A
ENGINE	Engine	PERKINS 1103A-33TG2	
	Engine emissions standard (REG. UE 2016/1628)	EU STAGE 0	
	RPM governor	Mechanical	
	Performance class (ISO8528-5)	G2	
	Rpm	1500	rpm
	Nr. of cylinders	3	
	Bore x stroke	105 x 127	mm
	Displacement	3300	cc
	Induction system	Turbocharged	
	Cooling system	Water	
	Engine net prime power	72,1 (53,8)	Hp (kW)
Exhaust gas aftertreatment	/		
CONSUMPTION	Fuel type	Diesel	
	Consumption @ 50-75-100% carico – load - charge	7,6 – 10,8 – 14,6	lt/h
	Standard tank capacity	100	lt
	Autonomy @ 75% carico – load - charge	9,2	h
ALTERNATOR	Alternator	STAMFORD – MECC ALTE – MARELLI MOTORI	
	Type	Self excited, brushless	
	Number of poles	4	
	Insulation class	H	
	Temperature rise class	H	
	Voltage regulation	AVR	
	Voltage precision	± 1	%
GENERAL	Sound level (soundproof version)	69	dB(A) 7mt
	Exhaust pipe diameter	60	mm
	Electrical system voltage	12	V

## ELECTRIC PANEL

### MANUAL

### AUTOMATIC MAINS FAILURE



<i>Electronic control unit with multimeter</i>	<b>LOVATO ELECTRIC RGK420SA</b>	<b>COMAP IntelliLite 9</b>
<i>Electrical panel enclosure protection degree</i>	<b>IP44</b>	
<i>ON-OFF electric panel switch</i>	<i>Key type. In-built the control unit</i>	<i>Without key</i>
<i>Emergency pushbutton</i>	<b>STANDARD</b>	
<i>Battery charge maintainer</i>	/	<b>12V 3A</b>
<i>Power supply</i>	<i>Full power terminal</i>	<i>Full power terminal</i>
<i>Circuit breaker</i>	<i>Magnetothermal type 4P 80A</i>	<i>Magnetothermal type 4P 80A</i>
<i>Main protection alarms</i>	<i>Min-max V and Hz. LOP. HWT. Battery charger alternator failure. Low fuel level</i>	

## STANDARD ELECTRONIC CONTROL UNIT

**LOVATO ELECTRIC  
RGK420 SA**



*Functions: manual start, remote start, periodic test*

*Multimeter V (L1, L2, L3, N), A (L1), Hz, kVA, battery V, hour counter*

*Backlit LCD display. Optical port and NFC*

**COMAP  
IntelliLite 9**



*Functions: automatic or manual start, remote start, periodic test*

*Multimeter V (L1, L2, L3, N), A (L1, L2, L3), Hz, kVA, battery V, hour counter*

*Backlit LCD display. USB port*

*Communication accessories available: Ethernet, GSM-GPRS, 4G, GPS*

## OPTIONAL ELECTRONIC CONTROL UNIT




**DEEP SEA DSE4520 MKII  
DEEP SEA DSE7320 MKII**





**COMAP AMF25**

## SOUNDPROOF AND WEATHERPROOF CANOPY



<i>Self-supporting frame material</i>	<i>Carbon steel sheet, electro-welded, minimum thickness 2,5 mm</i>
<i>Soundproof canopy material</i>	<i>Carbon steel sheet, electro-welded, thickness between 1,5 and 4,5 mm</i>
<i>Painting</i>	<i>Epoxy powder RAL 5015 textured, outdoor-proof</i>
<i>In-built fuel tank</i>	<b>100 lt + Drip tray</b>
<i>Soundproofing coating material</i>	<i>Polyurethane finished with water-repellent and anti-oil fabric. Fire resistance EN13501-1 class B</i>
<i>Muffler</i>	<i>In-built the canopy. Residential type with sound reduction 35 dB(A)</i>
<i>Access openings</i>	<i>n.2 doors with key lock</i>
<i>Electric panel</i>	<i>Short side position. Dedicated protective door with padlockable lock and porthole (only GS with automatic panel)</i>
<i>Fresh air intake and hot air expulsion</i>	
<i>Lifting system</i>	<i>n.4 lifting hooks</i>
<i>Support feet</i>	<i>n.4 support feet with holes for machine ground fastening</i>

## CONTAINER TRANSPORTABILITY ADVANTAGES

VERSION	20' BOX	40' BOX	40' HC
 <i>N. transportable pieces</i>	6	13	13
	6	13	26

## MAIN OPTIONS



90A automatic transfer switch (ATS)



200 lt bigger fuel tank with drip tray



750W engine preheating system



Electronic engine speed governor



Automatic fuel transfer kit with manual by-pass system



Residual current circuit breaker



Electric fuel floater to check the fuel level from the electronic control unit



Engine oil pressure and cooling water temperature measuring instruments

## OTHER OPTIONS

Power distribution socket set

Synchronizing electric panel

Battery switch

Remote control systems **ETHERNET, 2G - 3G - 4G, GPS**

Further alternator brand

Quick couplings for connecting an external tank with three way valve -

Outdoor, underground and transportable tanks

Slow or fast towing trailer

Front hot air expulsion canopy

Further colors

## VERSIONS WITH SPECIAL EQUIPMENT



### RENTAL

Special version with features designed for the rental market



### ZERO NOISE

Super sound-proofed special version, noise level 50, 55 or 60 dB(A)

**Greenpower AB**  
Helsingborgsvägen Varalöv,  
262 96 Ängelholm, Sweden  
Phone: +46 43122240  
Email: [info@greenpower.se](mailto:info@greenpower.se)  
Web: [www.greenpower.se](http://www.greenpower.se)