

**TECHNICAL DATA SHEET**

**GP77 TR/S**

**STRUCTURE**



Gear Box/alternator monoblock unit coupled through shaft, installed on a welded, powder-painted carbon steel base frame with demountable legs. (images are for illustrative purpose only)

**ELECTRIC PANEL**

Magnetothermic circuit breaker
Earth fault device
125A 400V Socket
32A 230V Socket
Schuko sockets 16A 230V
E31 digital module:
- Voltmeter
- Frequency meter
- Hour counter

**TECHNICAL DATA**

EQUIPMENT SPECIFICATION (ISO 8528/1)	50Hz
Prime power at cosfi 0.8	75 kVA
Prime power at cosfi 0.8	60 kW
Voltage available to the terminals	400/230 V
Dimensions (mm)	1140x750x1065
Weight (Kg)	454

GEAR BOX	50Hz
Brand and model	6005.407.035
R.P.M.	1500

ALTERNATOR	50Hz
Brand and model	MECC ALTE ECP32-3L/4 (*)
Synchronous with electronic governor voltage	± 1%
Pole	4
Stator/rotator insulation	H
Protection level	IP23
Continuous power	75 kVA

(\*) = or similar brand



**Greenpower AB**  
Helsingborgsvägen Varalöv  
262 96 Ängelholm  
Tel: 0431 - 222 40  
E-mail: info@greenpower.se  
web:www.greenpower.se